BN

Bureau de normalisation du Québec

BNQ 2622-126/2023

Concrete Pipes, Monolithic Lateral Connections and Related Parts Intended for Evacuation of Sanitary Wastewater and Storm Water



STANDARD

BNQ 2622-126/2023

Concrete Pipes, Monolithic Lateral Connections and Related Parts Intended for Evacuation of Sanitary Wastewater and Storm Water

Tuyaux, branchements latéraux monolithiques et pièces connexes en béton destinés à l'évacuation des eaux d'égout sanitaire et pluvial



Bureau de normalisation du Québec

The Bureau de normalisation du Québec (BNQ) is a standardization organization based in Quebec and created in 1961. It is one of the standards development organizations accredited by the Standards Council of Canada (SCC) and as such, is part of the National Standards System.

As an administrative unit of Investissement Québec (IQ), the BNQ produces standards that meet the needs of the industry, of public and para-public organizations, and of concerned groups.

THIRD EDITION — 2023-06-22

This new edition supersedes the edition dated April 1st, 2009.

This document is published in both French and English. In case of incompatibility, the French version prevails.

The decision resulting from the systematic review that will enable to determine whether the current document shall be modified, revised, reaffirmed or withdrawn will be implemented no later than at the end of June 2033.

ICS: 19.020; 23.040.50; 91.100.30.

ISBN 978-2-551-27002-6 (printed version) ISBN 978-2-551-27003-3 (PDF) Legal deposit — Bibliothèque et Archives nationales du Québec, 2023

REQUEST FOR INFORMATION AND PURCHASE

Any request for information or purchase of this document may be sent to the Bureau de normalisation du Québec (BNQ) at: 333, rue Franquet, Québec, Quebec G1P 4C7 Telephone: 418-652-2238, ext. 2437 or 1-800-386-5114; fax: 418-652-2292 Email: <u>bnginfo@bng.qc.ca</u>; website: <u>https://www.bng.qc.ca</u>

REVISION OF BNQ DOCUMENTS

Collaboration from BNQ document users is essential in keeping our documents up to date. Therefore, any suggestion aimed at improving their contents will be appreciated. We ask you to send us your suggestions or comments on the form at the end of this document.

The electronic or printed version of this document is for personal use only. Distribution to third parties, partners or clients, as well as saving, distribution or use on a computer network is forbidden without written agreement from the BNQ.

Only purchasers duly registered with BNQ Customer Service will receive document updates. Notifications and the catalogue may be consulted at all times on the BNQ's website [https://www.bnq.qc.ca] to verify if a more recent version of a document exists or if amendments or errata have been published.

If a registered purchaser wishes to continue to receive updates, the purchaser must inform BNQ Customer Service of any change of address as soon as possible.

This document is the result of thousands of hours of work provided on a voluntary basis by many community experts. We thank you for taking this into account, and for your contribution through your purchase of this document for its evolution in the years to come.

© BNQ, 2023

All rights reserved. Unless otherwise specified, no part of this document may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilming, without written permission from the BNQ.

NOTICE

UNDERSTANDING OF THE NOTION OF EDITION

It is important to note that this edition implicitly includes all amendments and errata that might be published separately at a later date. It is the responsibility of the users of this document to verify whether any amendments or errata exist.

INTERPRETATION

The verb **shall** is used to express a requirement (mandatory) in order to conform to this document.

The verb **should**, or the equivalent expressions **it is recommended that** and **ought to**, is used to indicate a useful, but not mandatory, suggestion or to indicate the most appropriate means of conforming to this document.

Except for notes presented as **normative notes**, which set out mandatory requirements and which appear in the lower portion of figures and tables only, all other **notes** are **informative** (non-mandatory) and provide useful information intended to facilitate understanding or clarify the intent of a requirement or to add clarification or further details.

Normative annexes provide additional requirements (mandatory) in order to conform to this document. **Informative annexes** provide additional (non-mandatory) information intended to assist in the understanding or use of elements of this document or to clarify its implementation. They contain no mandatory requirements for the purpose of compliance with this document.

DISCLAIMER OF RESPONSIBILITY

This document was developed as a reference document for voluntary use. It is the user's responsibility to verify whether the application of this document is mandatory under the applicable legislation or regulations or whether trade regulations or market conditions stipulate its use in, for example, technical regulations, inspection plans originating from regulatory authorities and certification programs. It is also the responsibility of the users to consider limitations and restrictions specified in the Purpose and Scope and to judge the suitability of this document for the user's purposes.

MARKING AND LABELLING REQUIREMENTS

This document may contain requirements for marking and/or labelling. In this event, in addition to meeting such requirements, it is also the responsibility of the suppliers of products to comply with the applicable national, provincial or territorial laws and regulations of the jurisdictions in which the products are distributed.



Suppliers

FOREWORD

This standard was developed in compliance with the Standards Council of Canada (SCC)'s Requirements and Guidance for standards development organizations. Its publication was approved by a Standards Development Committee, whose members were:

DUPONT, Éric	Lécuyer et Fils		
FOURNIER, Jean Kristian	Béton Brunet		
LASNIER, Nathalie	Tubécon		
PAQUET, Guy	Béton provincial		
TRUDEAU, Jean-François	Produits de ciment de Sherbrooke		
Users			
DUMEIGNIL, Sacha	Ville de Montréal		
LACHANCE, Dany	Association des ingénieurs municipaux du Québec (AIMQ)		
NAZAIR, Claude	Ministère des Transports et de la Mobilité durable (MTMD)		
RENAUD, Jean-François	Ville de Québec		
General Interest			
ABESQUE, Charles	Association des constructeurs de routes et grands travaux du Québec (ACRGTQ)		
GAGNÉ, Richard	Université de Sherbrooke		



GUINDON, Marie-Andrée	Cement Association of Canada (CAC)			
LOVRIC, Davor	Association des firmes de génie-conseil — Québec (AFG)			
Coordination				
LECRUX-TRUDEL, Sylvie (Standards Developer)	Bureau de normalisation du Québec (BNQ)			
Linguistic Review				
TREMBLAY, Carole (Editor)	Bureau de normalisation du Québec (BNQ)			
The participation of the following people is also worthy of mention:				
ALIBIN Carl	Tubécon			

Aobin, can	Tubecom
CAZA, Alain ¹	Béton Brunet
CHRÉTIEN, Éric	Béton provincial
GONZALEZ-LOZANO, Arsenio	Cement Association of Canada (CAC)
JACQUES, Paul-Francis	Ville de Montréal
LARIN, Éric	Béton Brunet
LIMA, Paula Luciana de Oliveira	Ministère des Transports et de la Mobilité durable (MTMD)
MAGRAMANE, Rabah	Ministère des Transports et de la Mobilité durable (MTMD)
MARCOUX, Alain	Ville de Québec

¹ At the time of publication of this standard, the aforementioned person no longer worked for this organization.



CONTENTS

				Page
1	PURPOSE			
2	SCOPE			1
3	NORMATIVE REFERENCES			2
	3.1 3.2	GENERAL DOCUME	NTS FROM STANDARDS BODIES	2 2
4	DEFINI	FIONS		3
5	CLASSIFICATION AND DESIGNATION			5
	5.1 5.2 5.3	GENERAL REINFOR UNREINF	CED CONCRETE PIPES ORCED CONCRETE PIPES	5 5 5
6	GENERAL REQUIREMENTS			5
	6.1 6.2	SHOP DRAWINGS MATERIALS		5 6
		6.2.1 6.2.2 6.2.3 6.2.4 6.2.5	Hydraulic binders Aggregates Steel Admixtures Mixing water	6 6 6 6
	6.3 6.4	OUTSIDE CURING	STORAGE OF MATERIAL	7 7
		6.4.1 6.4.2 6.4.3 6.4.4 6.4.5	General Steam Saturated absorbent canvas Sprinklers Combination of conditions	7 7 7 7 8
	 6.5 BELL AND SPIGOT ANGLE 6.6 FLOW LINE 6.7 ANNULAR SPACE 6.8 BELL AND SPIGOT JOINT AND RUBBER GASKET SEAL 			8 8 8 8



	6.9 CHARACTERISTICS OF RELATED PARTS6.10 LUBRICANT				
7	SPECIFIC REQUIREMENTS				
	7.1	REINFORCED CONCRETE PIPES			
		7.1.1 7.1.2 7.1.3 7.1.4 7.1.5 7.1.6 7.1.7 7.1.8 7.1.9 7.1.10	General Surface of elements Lift holes Dimensional tolerances Steel reinforcement Resistance to load $D_{0.3}$ Resistance to load D_{ult} Air leak tightness of rubber gasket seals for sanitary sewer pipes of nominal diameter exceeding 750 mm Resistance to exfiltration for sanitary sewer pipes of nominal diameter less than or equal to 750 mm Air leak tightness of lift holes plugging for sanitary sewer pipes of nominal diameter exceeding 900 mm	9 9 10 10 11 12 12 13 13 13	
	7.2	UNREINF	FORCED CONCRETE PIPES	13	
		7.2.1 7.2.2 7.2.3 7.2.4 7.2.5 7.2.6	General Appearance of elements of surface Lift holes Dimensional tolerances Resistance to load D _{ult} Resistance to exfiltration of sanitary sewer pipes	13 13 14 14 14 14	
8	SAMPLING			15	
	 8.1 COLLECTION OF SAMPLES 8.2 VISUAL INSPECTION OF SAMPLES 8.3 CONDITIONING OF SAMPLES 			15 15 15	
9	INSPECTION AND TEST METHODS				
	9.1	INSPECT	ION OF DIMENSIONAL CHARACTERISTICS	15	
		9.1.1 9.1.2 9.1.3 9.1.4	General Lengths Internal and external diameters Wall thickness	15 15 15 16	
	9.2	.2 STRENGHT TESTS UNDER LOAD $D_{0.3}$ AND UNDER LOAD D_{ult} USING THE THREE-EDGE-BEARING TEST METHOD		16	
		9.2.1 9.2.2 9.2.3 9.2.4	Specimens Apparatus Procedure Calculation and presentation of results	16 16 17 18	



		9.2.5	Repeat test	19
	9.3	HYDROS	TATIC TEST	19
		9.3.1 9.3.2 9.3.3	General Specimens Procedures	19 19 19
	9.4	LOW-PR	ESSURE AIR TEST FOR LEAKAGE	20
		9.4.1 9.4.2 9.4.3	General Air leak tightness of rubber gasket seals Air leak tightness of lift holes	20 20 20
10	MARKI	NG		21
Table :	1 —	Rein	forced concrete pipes: resistance to load $D_{0.3}$ and to load D_{ult}	22
Table 2	2 —	Unre	einforced concrete pipes: minimum thickness and minimum resistance to load D_{ult}	23
Table	3 —	Max G	imum acceptable surface areas of non-structural repairs based on pipes diameters, monolithic lateral connections or related parts	24
Table 4	4 —	Class	I to V reinforced concrete pipes: dimensional tolerances	25
Table !	5 —	Rein	forced concrete pipes and related parts: tolerances on internal manufacturing dimensions	26
Table (6 —	Rein r r	forced concrete pipes: low-pressure air test for leakage on rubber gasket seals of pipes — Example of the amount of time required for a pressure loss [drop time] (t) for internal diameters (d) from more than 750 mm to 3 600 mm	27
Table	7 —	Unre	inforced concrete pipes: dimensional tolerances	28
Table 8	8 —	Diffe r	rential loading for the hydrostatic test applicable to pipes with nominal diameters less than 900 mm	29
Table 9	9 —	Spac I	e between the inside faces of the lower bearing strips based on pipe diameter	30
Figure	1 —	Bell ເ	and spigot angle and annular space in reinforced and unreinforced concrete pipes	31
Figure	2 —	Rubb r	per gasket seal area where it is possible to perform non-structural repair in the case of concrete chippings on the spigot or the bell of an element	32
Figure	3 —	Mea t	surement of the levelling deviations inside a pipe and along its otal length	33
Figure	4 —	Dete	rmination of the deviation from straightness	34
Figure	5 —	Leng	th: two diametrically opposite sides	34



Bearing strips: strength test and crushing strength test using the three-edge-bearing test method		
Gauge to measure cracks	36	
Pipes with a bell: strength test and crushing strength test using the three-edge-bearing test method		
Pipes without a bell: strength test and crushing strength test using the three-edge-bearing test method		
Pipes with a cut off bell: strength test and crushing strength test using the three-edge-bearing test method	39	
Characteristics of the monolithic lateral connections	40	
RUBBER GASKET SEALS		
 Physical characteristics of the rubber gasket seals 	41	
LISTE OF MINIMUM INFORMATION THAT SHALL BE INCLUDED IN A SHOP DRAWING FOR PIPES AND MONOLITHIC LATERAL CONNECTIONS	42	
LIST OF MINIMUM INFORMATION THAT SHALL BE INCLUDED IN A SHOP DRAWING FOR RELATED PARTS	44	
MAIN CHARACTERISTICS OF THE REINFORCED CONCRETE PIPES FOR TRENCHLESS INSTALLATIONS	46	
 Types of characteristics of the pipes to be specified by the design engineer of the project according to the trenchless installation method used 	47	
ORDER PREPARATION	49	
EXAMPLES OF CALCULATIONS OF RESISTANCE TO LOAD $D_{0.3}$ AND LOAD D_{ult}	50	
INFORMATIVE REFERENCES	51	
	 Bearing strips: strength test and crushing strength test using the three-edge-bearing test method Gauge to measure cracks Pipes with a bell: strength test and crushing strength test using the three-edge-bearing test method Pipes without a bell: strength test and crushing strength test using the three-edge-bearing test method Pipes with a cut off bell: strength test and crushing strength test using the three-edge-bearing test method Characteristics of the monolithic lateral connections RUBBER GASKET SEALS Physical characteristics of the rubber gasket seals LISTE OF MINIMUM INFORMATION THAT SHALL BE INCLUDED IN A SHOP DRAWING FOR PIPES AND MONOLITHIC LATERAL CONNECTIONS LIST OF MINIMUM INFORMATION THAT SHALL BE INCLUDED IN A SHOP DRAWING FOR RELATED PARTS MAIN CHARACTERISTICS OF THE REINFORCED CONCRETE PIPES FOR TRENCHLESS INSTALLATIONS Types of characteristics of the pipes to be specified by the design engineer of the project according to the trenchless installation method used ORDER PREPARATION EXAMPLES OF CALCULATIONS OF RESISTANCE TO LOAD D_{0.3} AND LOAD D_{ult} INFORMATIVE REFERENCES 	



CONCRETE PIPES, MONOLITHIC LATERAL CONNECTIONS AND RELATED PARTS INTENDED FOR THE EVACUATION OF SANITARY WASTEWATER AND STORM WATER

1 <u>PURPOSE</u>

This standard specifies the physical and dimensional characteristics of prefabricated reinforced concrete and unreinforced concrete pipes, monolithic lateral connections and related parts. This standard also specifies inspection and test methods to verify these characteristics.

2 <u>SCOPE</u>

This standard applies to round sections of reinforced concrete or unreinforced concrete pipes intended for conveying sanitary wastewater or storm water or both by gravity flow. These pipes may also be used as culverts.

This standard applies to reinforced concrete pipes and monolithic lateral connections of diameters from 200 mm to 3 600 mm, to unreinforced concrete pipes and monolithic lateral connections of diameters from 150 mm to 900 mm and to reinforced concrete or unreinforced concrete related parts.

NOTES —

- 1 For requirements concerning the installation of concrete sewer pipes, it is recommended to refer to the standardized specification BNQ 1809-300. The document ASTM C1840/C1840M explains the interpretation of the different visual aspects to consider during the inspection of reinforced concrete or unreinforced concrete pipes already installed.
- 2 For requirements concerning trenchless installation, the main characteristics of reinforced concrete sewer pipes to be specified by the design engineer of the project are described in Annex D of this standard.
- 3 For requirements concerning the installation of culverts made of concrete pipes, it is recommended to refer to the *Cahier des charges et devis généraux Infrastructures routières Construction et réparation* of the Ministère des Transports du Québec.